

# ATTESTATION OF CONFORMITY

Issued to: EXIOM SOLUTION S.A.  
Building C, Zone 2, Electronic Industrial Park, Demonstration Area, 476000 Shangqiu  
City, Henan, China.

For the product: Crystalline Silicon PV Modules

Trade name: EXIOM  
Type/Model: see annex for details

Ratings: Maximum System Voltage: 1500 V; Protection Class: Class II; Pollution Degree: 1

Manufactured by: EXIOM SOLUTION S.A.  
Building C, Zone 2, Electronic Industrial Park, Demonstration Area, 476000  
Shangqiu City, Henan, China

Requirements: EN 61215-1:2016  
EN 61215-1-1:2016  
EN 61215-2:2017  
EN IEC 61730-1:2018  
EN IEC 61730-1:2018/AC: 2018-06  
EN IEC 61730-2:2018  
EN IEC 61730-2:2018/AC: 2018-06

This Attestation is granted on account of an examination by DEKRA, the results of which are laid down in a confidential file no. 6122626A.51A and 6122626A.51B.

This Attestation implies that the examined types are in accordance with the standards designated under the Low Voltage Directive (LVD) 2014/35/EU.

The examination has been carried out on one single specimen or several specimens of the product, submitted by the manufacturer. The Attestation does not include an assessment of the manufacturer's production. Conformity of his production with the specimen tested by DEKRA is not the responsibility of DEKRA.

The CE marking may be affixed on the product if all relevant and effective EC directives are complied with.

Shanghai, 2 November 2022

Number: 6122626.02AOC

DEKRA Testing and Certification (Shanghai) Ltd.

  
Cliff Lin  
Certification Manager

© Integral publication of this attestation and adjoining reports is allowed

Page 1 of 2



# Annex

---

Document no. : 6122626.02AOC  
Fire Rating: : Class C according to UL790

**Product data – type EXxxxM-72(HC)(182)**

Description : xxx=250-300, in steps of 5, 72 half cut cells

**Product data – type EXxxxM-96(HC)(182)**

Description : xxx=305-375, in steps of 5, 96 half cut cells

**Product data – type EXxxxM-108(HC)(182)**

Description : xxx=380-425, in steps of 5, 108 half cut cells

**Product data – type EXxxxM-120(HC)(182)**

Description : xxx=430-470, in steps of 5, 120 half cut cells

**Product data – type EXxxxM-144(HC)(182)**

Description : xxx=520-560, in steps of 5, 144 half cut cells

---

End